

Oil refresh



0,4L

As with all wood finishing always do a test area first to safeguard against an undesirable outcome. This technical data sheet is merely a guide and not a guarantee. All products are formulated to the best of our knowledge. The information is given as a result of many years experience. This product has had extensive tests carried out.

Produced by Debal Coatings nv
Industrieweg 29 - 8800 Beveren-Roeselare
Belgium
tel. +32 (0) 51 30 11 40
fax +32 (0) 51 31 26 48
ciranova@ciranova.be

PRODUCT DESCRIPTION

Universal maintenance system for oiled wooden floors. For the maintenance of floors treated with flooring oil and UV-oil.

TECHNICAL DATA

APPEARANCE	fluid
COLOUR	uncolored
SOLID CONTENT	26%

USE

To maintain floors treated with Hardwaxoil and UV-oil.

PREPARATION

Clean the floor or furniture with a wet cloth. Treat heavy dirt with Intensive Cleaner Ciranova®.

USER TIPS

Shake well before use. Apply Oil Refresh Ciranova very thin and evenly. Let the oil impregnate a few minutes. Afterwards sweep the surface with a dry and non fluffy cloth.



DRYING TIMES

Do not charge the first 12 hours!
The optimal hardness is reached after 48 hours. Don't use any water or maintenance products during this period.



APPLYING QUANTITY

50 m²/l for the maintenance of already threatened wooden floors.

AFTER TREATMENT

It's recommended to treat each form of damage with Oil Refresh Ciranova®.

SPECIAL QUALITIES

Used cloths need to be thrown into water after use, to increase flammability. The presence of linseed oil in the system causes this measure. Oil Refresh Ciranova® protects your parquet floor against water and your wood gets a natural view.