

Reactive stain



5L 1L

As with all wood finishing always do a test area first to safeguard against an undesirable outcome. This technical data sheet is merely a guide and not a guarantee. All products are formulated to the best of our knowledge. The information is given as a result of many years experience. This product has had extensive tests carried out.

Produced by Debal Coatings nv

Industrieweg 29 - 8800 Beveren-Roeselare
Belgium
tel. +32 (0) 51 30 11 40
fax +32 (0) 51 31 26 48
ciranova@ciranova.be

PRODUCT DESCRIPTION

Ageing stain based on natural and chemical dyes.

TECHNICAL DATA

COLOURS	available in 16 colours
LUSTRE	-
DENSITÉ	+/- 1,00 kg/l
VISCOSITY	like water

USE

Reactive stains are particularly suitable for wood containing tannin such as oak and pine. For interior use only.

PREPARATION

Sand the wood. Remove carefully sanding dust.

USER TIPS

Before use stir and shake well. Apply the reactive stain with a brush in the direction of the fiber and equalize with a dry brush. Attention: It's a reactive stain, apply the stain equally!



DRYING TIMES

6 hours at room temperature. (reaction time)



APPLYING QUANTITY

- 7-12 m²/l. Depending on type of wood and the sanding.

AFTER TREATMENT

Sand with fine sanding paper after drying. Can be treated afterwards with wax or oil. For Vanish, please contact our technical service.

PRODUCT INFORMATION

16 colours available.

Storage life: 1 year in original and well closed packaging
Must be stored in a frost free place.

SPECIAL QUALITIES

Only use stainless material. After use, clean the material with water. This product should not be poured into drains.

Stains should always be tested before the surface treatment. Used sanding grain, type of wood, may affect the final colour.