

EXTERIOR WOOD VARNISH

Varnish for exterior and interior woodwork. EXTERIOR WOOD VARNISH is applied to vertical woodwork.

- » Odorless
- » Highly concentrated anti-UV
- » High resistance
- » Excellent adhesion to exotic woods
- » Exterior / Interior

TECHNICAL DATA

Product type

waterbased

Cleaning tools

water

Coverage

+/- 12 m²/l

Drying time

Between 2 coats : 3 hours

Drying to the core

48 hours

Transport

between 5°C and 25°C

Waste

dispose of waste and empty packaging in accordance with local regulations.



2,5L



PROTECTION

EXTERIOR

PRE-TREATMENT

Use EXTERIOR WOOD VARNISH on clean, dry wood, free of flaking varnish or old paint. Remove cracked varnish or paint if necessary.

Sanding the surface (120-grit sandpaper) will facilitate penetration. For exterior applications, it is recommended to round off sharp corners of woodwork (120-grit sandpaper) to achieve a perfect coating..

APPLICATION

Ready to use, do not dilute.

Apply with a brush or roller (for large surfaces) in 3 even, even coats.

2 coats will be sufficient for interior wood.

Between coats, it is recommended to sand by hand (120-grit sandpaper) and dust again. This will also ensure good adhesion and provide a smooth, attractive surface that is easy to maintain. Do not use steel wool..

MAINTENANCE

EXTERIOR WOOD VARNISH is self-renovating. Sanding the surface (120-grit sandpaper) is essential. After dusting, apply two coats.

Periodic cleaning with EXTERIOR MAINTENANCE CLEANER